

NEOFLEX® PVC are highly flexible triple layer PVC hoses with integrated crosslinked and longitudinal reinforcement. Certified in Denmark, Norway and Sweden for use in technical water supply systems to max 25°C (See technical specifications for details).



Technical specifications :

Article no.	S212	S419	S420	S421	S422
Nominal size	DN6	DN10			
Inside diameter hose	Ø7,5	Ø10,0			
Outside diameter hose, without braiding	Ø12,3	Ø16,4			
Colour	White	White	Grey	White	Grey
Surface	Smooth	Smooth	Smooth	Ribbed	Ribbed
Braiding – bandwire	-	-	-	-	-
PVC coating	-	-	-	-	-
Max. work pressure	10 bar				
Max. temperature	25°C				
Min. flow at 3 bar	21 l/min	45 l/min			
Approvals	VA (DK) – SINTEF (N) - RISE (S)				

Standard fittings :

	Female elbow			Female			Male			Female nylon	Elbow nylon	
	3/8"	1/2"	3/4"	3/8"	1/2"	3/4"	1/4"	3/8"	1/2"	3/4"	3/4"	3/4"
DN6				x	x	x		x	x			
DN10	x	x	x	x	x	x	x	x	x	x	x	x

(Other fittings on request)

Applications* :



Dish washer



Washing machine



Toilet

*For other purposes, please contact Neoperl Nordic A/S