

Softpex® are highly flexible soft pex hoses with stainless steel braiding. Excellent functional, mechanical and hygienic properties. Certified in Denmark, Norway, Sweden, Germany and Great Britain, Holland (among others) for use in drinking water supply systems (according to European Standard EN13618).



Technical specifications :

Article no.	S141	S147	S148	S241	S247	S248	S441	S541	S641
Nominal size	DN6			DN8			DN10	DN13	DN15
Inside diameter hose	Ø6,4			Ø8,2			Ø10	Ø12,7	Ø15,5
Outside diameter hose, without braiding	Ø9,0			Ø11,0			Ø13,6	17,1	Ø20,5
Braiding	Stainless steel								
PE coating	-	Transp.	Grey	-	Transp.	Grey	-	-	-
Max. work pressure	10 bar								
Max. temperature	70 °C								
Min. flow at 3 bar	16 l/min			28 l/min			45 l/min	60 l/min	96 l/min
Approvals	GDV (DK) - VA (DK)- SINTEF (N)- RISE (S) – DVGW (DE) – WRAS (UK) – KIWA (NL) ... and others								

Standard fittings :

Female elbow	Female		Tube				Male long		Male short		Male			Comp. joint						
3/8"	1/2"	3/4"	3/8"	1/2"	3/4"	Ø8	Ø10	Ø12	Ø15	M8x1	M10x1	M8x1	M10x1	3/8"	1/2"	3/4"	Ø8	Ø10	Ø12	Ø15
DN6			x	x		x	x			x	x	x	x	x	x		x	x		
DN8	x	x	x	x	x		x	x			x		x	x				x	x	
DN10	x	x	x	x	x			x							x	x				x
DN13		x	x		x				x						x	x				
DN15			x		x				x							x				

(Other fittings on request)

Applications* :



Wash stand



Kitchen faucet



Toilet



Health care



Washing machine



Dish washer



Refrigerator

*For other purposes, please contact Neoperl Nordic A/S