

The Onity glass door solution is ideal for main entrance, office, meeting or passage doors, for virtually any type of property. It has been designed especially to fit the Onity electronic lock range on glass doors. This enables offering a comprehensive locking solution which includes any type of door in the building.

Electronic Features

- Compatible with Onity Trillium Mag, Trillium RFID and HT series electronic locks
- Works with Onity HT22, OnPoint and HT24W electronic locking systems
- Multiple card technologies:
 - Mag-stripe, Lo-Co and Hi-Co
 - Smart (chip)
 - RFID MIFARE® Classic/EV1, MIFARE Plus and Ultralight C
- Same electronic features as standard compatible Onity locks

Mechanical Features

- Lock Weight (mortise included): 4.7 kg
- Mortise dimensions: 291.7 x 103.5 x 29.5 mm
- EURO mortise profile (5470H)
- Backset: 50 mm
- Anti-thrust latch
- Panic function
- For new tempered glass door installation only (tempered glass cannot be re-worked)
- Also suitable for other types of doors with thickness under 25 mm (metallic, hard wood, lockers, etc.)
- Finish: Satin chrome

Options

- Key override (hidden or visible)

Certifications

- Directive 2014/30/EU (Electromagnetic Compatibility)
- Directive 2014/53/EU (R&TTE) *

* Only for RFID locks

